















INDUSTRIAL PRODUCTS LINEUP CHART

	MOBILE SHELVING SYSTEMS		MOBILE RACKING SYSTEMS				
	MOBILEX®	SAFEAISLE®	BULK&ROLL™	RACK&ROLL™ 8MA, 8P	HD 16MA	SAFERAK® 32P	SAFERAK® 60P
	1,000 lb per linear foot (1,488kg per linear meter) 	1,000 lb per linear foot (1,488kg per linear meter) 	2,400 lb per section (1,089kg per section) 	8,000 lb (3,629 kg) per single deep rack section  OPTIONAL 16,000 lb (7,258 kg) per double deep rack sections with tandem carriages 	16,000 lb (7,258 kg) 	32,000 lb (14,154 kg) per double deep rack sections with tandem carriages  OPTIONAL 16,000 lb (7,258 kg) per single deep rack section 	60,000 lb (27,216 kg) per double deep rack sections with tandem carriages  OPTIONAL 30,000 lb (13,608 kg) per single deep rack section 
SHELVING							
 SMARTSHELF 4-Post Hybrid Shelving	✓	✓		-	-	-	-
RACKING							
 4D Wide Span Bulk Storage Mini-Racking	✓	✓	✓	✓	✓	-	-
 TIRERAK Light-Duty Racking	-	-	-	✓	✓	-	-
 PALLET RACKING Provided by Others	-	-	-	✓	✓	✓	✓

SOME TECHNICAL VALUES MAY CHANGE DUE TO SEISMIC ZONE CRITERIA. PLEASE CONTACT YOUR FACTORY REPRESENTATIVE.

LEGEND


 Single Carriages
Mechanical-Assist
Shelving System


 Single Carriages
Powered-Electrical
Shelving System


 Single Carriages
Mechanical-Assist
Racking System


 Tandem Carriages
Mechanical-Assist
Racking System


 Single Carriages
Powered-Electrical
Racking System


 Tandem Carriages
Powered-Electrical
Racking System


MA = Mechanical Assist



P = Powered Electrical



Powered mobile control for
SAFERAK® 32P and 60P.

SHELVING & RACKING DIMENSIONS & CAPACITY									ADD-ONS
MAX. HEIGHT	MAX. WIDTH	MAX. DEPTH	MAX. LOAD CAPACITY per Shelf or Beam (lb and kg)	MAX. LOAD CAPACITY per Bay (lb and kg)	INCREMENTS	SHELF ATTACHMENT	POST DIMENSIONS	CROSS-BRACING	INDUSTRIAL DRAWERS 400 lb (181 kg) 
SHELVING									
SMARTSHELF 4-Post Hybrid Shelving	120" (3.05 m)	48" (1.22 m)	24" (0.61 m)	Up to 300 lb (136 kg) with hooks Up to 500 lb (227 kg) with shelf supports and	Up to 2,000 lb (907 kg)	1" or 1 1/2" (25.4 mm or 38.1 mm)	Hooks or Supports	1 1/4" x 1 1/2" (31.8 mm x 38.1 mm)	✓
RACKING									
4D Wide Span Bulk Storage Mini-Racking	240" (6.096 m)	96" (2.44 m)	48" (1.22 m)	Up to 1,500 lb (680 kg)	Up to 4,500 lb (2041 kg)	2" (50.8mm)	Beams	2" x 1 5/16" (50.8 mm x 33.3 mm)	-
TIRERAK Light-Duty Racking	240" (6.10 m)	108" (2.74 m)	48" (1.22 m)	Up to 1,000 lb (454 kg)	Up to 6,000 lb (2722 kg)	1.5" (38.1mm)	Beams	2" x 1 3/4" (50.8 mm x 44.5 mm)	-
PALLET RACKING Provided by Others	288" (7.315 m)	144" (3.66 m)	60" (1.52 m)	Up to 12,000 lb (5 443 kg)	Up to 30,000 lb (13,608 kg)	3" (76.2mm)	Beams	Varies	-

CARRIAGES HEIGHT

